

Jeep Cable for monitoring at Studios <SJP Series>


Applications

Please use as monitor corresponding to HDTV in broadcasting studios.


Features

- The multiple cable possible to connect by one piece of cable, in combination with HD-SDI signal, AC 100V power source, audio signal and control signal, for monitor corresponding to HDTV.
- TACHII have employed 5CFWS newly developed for transmission of HD-SDI signal, so that our customers can enjoy higher anti-flexion property and flexibility of cable as well as easier handling and storing in the broadcasting studios.
- The stable power supply can be assured with allowance against big size plasma and liquid crystal monitor, because of securing 1.5mm² substantially with 0.75mm²×4 pieces power cable(upto maximum allowable current 15A under ambient temperature 30°C)
- Please see the respective pages mentioned in the following Unit Configuration for the specification details except power source unit .
- The products are available whichever you like the cable only or the cable with ends-processed. Please ask our sales staffs about the delivery style.
- The recommendable distance for transmission of HD-SDI signal is max.80m. Please use with allowances in cable length considering the attenuation property. (Please refer to nominal attenuation and EYE-pattern on Page 9).
- Pb free type PVC materials have been employed for power source insulation, unit sheath and jackets, considering environment-friendly.

Unit Configuration



Finished Product Configuration



Construction

Model	Unit structure				Layer strands		Finished product				Stock available				
	Unit O.D. mm				Pitch mm	O.D. mm	O.D. mm	Approx. weight kg							
	6.8	4.4	7.1	6.0				20m	30m	50m	70m	20m	30m	50m	70m
SJP-HP	5CFWS (H)		power Source 1.5 SQ × 2 (P)	T-4E6S	abt.210	14.1	17.0	6.0	9.0	14.9	20.8	○	○	○	◎
SJP-HVP	5CFWS (H)	3C2VS (V)	power Source 1.5 SQ × 2 (P)		abt.210	14.1	17.0	6.5	9.8	16.2	22.7	○	○	○	◎
SJP-HPA	5CFWS (H)		power Source 1.5 SQ × 2 (P)	T-4E6S (A)	abt.220	14.6	17.8	7.1	10.6	17.6	24.6	○	○	○	◎
NEW SJP-H3P	5CFWS (H, G, B)		power Source 1.5 SQ × 2 (P)		abt.310	17.0	20.2	9.3	13.9	23.2	32.5	◎	◎	◎	◎

○ Standard ◎ Custom-made Other length available on request